

ESTERTEC®

VSP Synthetic Esters




ZSCHIMMER & SCHWARZ

A NEW SYNTHETIC ESTER PRODUCT TECHNOLOGY IS NOW AVAILABLE

EsterTec® vicinal secondary polyol (VSP) esters offer exceptional performance based on their innovative structure achieved via a unique production process. Utilizing standard raw materials that are globally accessible, these esters ensure high stability through vicinal ester molecular positioning. Steric hindrance enhances oxidative stability, while secondary alcohols on adjacent carbons significantly improve hydrolytic stability. Experience the next level of synthetic lubricant performance by formulating with EsterTec VSP diesters.

VICINAL SECONDARY POLYOL (VSP) ESTER



ESTERTEC VSP: BEST-IN-CLASS SYNTHETIC LUBRICANT BASE STOCK DESIGNED FOR OUTSTANDING PERFORMANCE VALUE AND RELIABILITY

With a broad viscosity range and operating temperature window, EsterTec affords superior control of friction and reduces wear, ensuring the stability and long life of high-performance lubricants. This advanced component is miscible with PAO and petroleum-based stocks, as well as compatible with standard elastomers and seals. EsterTec excels in heat transfer, features excellent dielectric properties, and exhibits high flash and fire points for enhanced safety in both lubricant and electrical insulating fluid applications. Environmentally friendly, with a high biogenic content, EsterTec is readily biodegradable and USDA BioPreferred, making it a top choice for those seeking efficiency and sustainability on their ESG scorecard.

BENEFIT FROM ALL THE PERFORMANCE ADVANTAGES OF A DIESTER OR POLYOL ESTER, PLUS EXCEPTIONAL BENEFITS THAT SET THIS TECHNOLOGY APART:

- **Natural Energy Efficiency:** Leverage their low density, high viscosity index, and superior lubricity, for enhanced energy savings.
- **Best-in-Class Stability:** Enjoy an unparalleled combination of oxidative, thermal, and hydrolytic stability, optimized for extended product life and consistent performance in applications that experience high temperatures or water ingress.
- **Optimal Heat Transfer and Dielectric Properties:** Achieve excellent thermal management and dielectric insulation, which can be leveraged in EV cooling applications.
- **High Biogenic Content:** Choose an environmentally friendly option that has a higher biogenic content compared to many synthetic diester or polyol esters.
- **Cost-Effective:** Save more due to lower-cost-per-unit volume. Molecular design leads to significantly lower density compared to standard esters.

EsterTec VSP sets the standard for a new class of polyol ester that delivers a blend of high performance, efficiency, sustainability, and outstanding value.

- **Wide Temperature Operating Range:** Reliable operation from -60°C to 240°C, enhancing low-temperature viscometrics and high-temperature stability.
- **Enhanced Friction and Wear Control:** Improved protection for components, reducing maintenance costs and downtime.
- **Energy Efficiency:** Lower energy consumption, translating to significant savings over time.
- **Environmentally Friendly:** A sustainable choice for next-generation lubricant formulations.

PERFORMANCE DATA

EsterTec
synthetic esters

EsterTec VSP: Advanced synthetic lubricant technology
that delivers across every performance metric

ESTERTEC VSP PRODUCT RANGE

PRODUCT NAME	ESTERTEC 2N-1416	ESTERTEC 2LN-1418	ESTERTEC 2G-1432	ESTERTEC 7GX-1446	ESTERTEC 7GX-1468	ESTERTEC 8LX-14150
KV100, cSt	3.6	4.1	6.8	9	11	18
KV40, cSt	16	18	32	46	68	150
Viscosity Index	115	125	180	165	155	130
Pour Point, °C	-60	-40	-42	-40	-40	-30
Density	0.895	0.893	0.890	0.900	0.915	0.935
NOACK Volatility, %	9	7	1	1	1	1
Biogenic Content, %	64	65	74	60	50	30
Oxidative Stability	✓	✓	✓	✓	✓	✓
Hydrolytic Stability	✓	✓	✓	✓	✓	✓
Friction/Wear Reduction	✓	✓	✓	✓	✓	✓
Energy-Efficiency Advantage	✓	✓	✓	✓	✓	✓
Cost/Performance Advantage	✓	✓	✓	✓	✓	✓



FIELDS OF APPLICATION

EsterTec excels in numerous fields of application, delivering exceptional performance, value, and reliability across various industries, including:



METALWORKING
FLUIDS



HYDRAULIC
FLUIDS



ENGINE OILS



COMPRESSOR
FLUIDS



BEARING
LUBRICANTS



GEAR OILS



H1 FOOD-GRADE
LUBRICANTS



GREASES



TRANSMISSION
FLUIDS



DRILLING MUD
LUBRICANTS



EALS FOR ENVIRONMENTALLY
SENSITIVE APPLICATIONS



TRANSFORMER
OILS



MULTIFUNCTIONAL
DIELECTRIC/
COOLANT/LUBRICANTS



OVEN CHAIN
OILS



COMPUTER
IMMERSION
COOLING

SUPERIOR PERFORMANCE


EsterTec VSP esters can be used to optimize premium synthetic lubricant formulations for use in high-performance applications. Technical and economic benefits include:

- **Oxidative Stability:** Resists degradation at high temperatures, minimizing deposits and sludge formation; noncorrosive to iron, aluminum, or copper.
- **Hydrolytic Stability:** Remains stable and effective even in the presence of moisture from condensation or contamination; achieves effective long-life performance in aqueous metalworking fluids.
- **Friction/Wear Reduction:** Minimizes energy losses due to friction, improving energy efficiency.
- **Energy Efficiency:** Low density that leads to decreased pumping energy requirements and reduced weight in mobile applications; helps conserve energy usage compared to standard lubricants.
- **Cost-Effectiveness:** Affords favorable total cost of ownership through its efficiency and performance results; lower density = lower shipping costs.
- **Eco-Friendliness:** High biogenic content, readily biodegradable, and low aquatic toxicity, making EsterTec VSP esters the preferred choice for EAL formulations.

ESTERTEC DELIVERS PERFORMANCE THAT IS EQUAL TO OR BETTER THAN STANDARD POLYOL ESTERS IN THE FOLLOWING AREAS:

- Pour Point
- Flash Point
- Foam Tendency
- Demulsibility
- Copper Corrosion
- Oxidative Stability
- Thermal Stability
- Specific Heat
- Thermal Conductivity
- Odor
- Color
- Clarity
- Miscibility with PAO
- Compatibility with Elastomers

ESTERTEC COMPARISON RADAR CHART



EsterTec VSP: Cutting-Edge Synthetic Ester Lubricant Technology

EsterTec VSP esters are the latest advancement in synthetic ester molecular design, meticulously created to deliver versatile and reliable functionality. Through its innovative molecular structure and production process, this synthetic lubricant component offers:

Superior Stability: Exceptional resistance to oxidation, thermal breakdown, and hydrolysis, for extended service life

Excellent Control of Friction and Wear: A unique molecular design that enables a balance of polar attraction to metal interfaces and surface packing under EHL conditions that reduce the coefficient of friction

Broad Operating Temperature Range: Lubricants formulated with VSP esters for cold temperature applications exhibit low dynamic viscosity and an excellent pour point, ensuring reliable performance in extreme conditions. For high-temperature applications, VSP esters offer low volatility and a high flash point, enhancing product durability and safety. The excellent viscometric properties of EsterTec VSP contribute to improved energy efficiency, making them the ideal solution for demanding industrial, automotive, and dielectric applications.



ZSCHIMMER & SCHWARZ

Chemistry tailor-made

► AMERICAS

Zschimmer & Schwarz, Inc.

70 GA Highway 22 W
Milledgeville, GA 31061 | US
T +1 478 454 1942
lubricants@zschimmer-schwarz.com

Zschimmer & Schwarz

do Brasil Ltda.
Estrada Geral Morro do Paula 546
Distrito Industrial – Bairro São Borja
93032-530 São Leopoldo RS | BR
T +55 51 3566 1666
zsb@zschimmer-schwarz.com.br

zslubes.com
zschimmer-schwarz.com

► EUROPE

Zschimmer & Schwarz

Italiana S.p.A.
Via Angelo Ariotto, 1/C
13038 Tricerro (VC) | IT
T +39 0161 808 111
info.zsi@zschimmer-schwarz.com

Zschimmer & Schwarz

España, S.L.U.
Ctra. CV-20, km. 3,200. Apdo. 118
12540 Vila-real (CS) | ES
T +34 964 626 365
info.zse@zschimmer-schwarz.com

Zschimmer & Schwarz

GmbH & Co KG Chemische Fabriken
Max-Schwarz-Strasse 3–5
56112 Lahnstein | DE
T +49 2621 12-0
info@zschimmer-schwarz.com

► ASIA

Zschimmer & Schwarz

Chemical (China) Co., Ltd.
No. 16, Kaiyuan Road
Datang Industrial Park
Sanshui, 528143 Foshan, Guangdong | CN
T +86 757 87 27 06 01
zsc@zschimmer-schwarz.cn



For further information,
please visit **estertec.com**